



VAPOR RECOVERY COUPLER CAMLOCK

Mod. 1520



APPLICATION

Vapor recovery coupler CAMLOCK 4" is used in the vapor recovery line (Stage 1) according to Directive ATEX 2014/34/UE and harmonized standard.

The 1520 Vapor Recovery Coupler is a 100-mm (4") female camlock coupler that is designed to be connected to any hose adapter and allows the vapor transfer to the tank truck during loading operation. It guarantee security for the operator.



CE Ex II 3 G

CHEMICAL SUITABILITY

- Aluminium standard Model is for tradition fuel and compatible chemical products.

| | |
|------------------------------|-----------------|
| CODE | 1520-00 |
| BODY | ALUMINIUM |
| PIN | BRASS |
| GASKET/OR | NBR |
| COUPLER SIZE | CAM-LOCK 4" |
| FITTING END SIZE | 3"M-2"1/2F BSPP |
| PRESSURE TEST | 0,5 bar |
| OPERATING TEMPERATURE | -20°/+60°C |

INSTALLATION

- For correct installation follow the Directives and product User Manual.
- For custom application or maintenance write to: quality@ridart.it.
- Declaration of Conformity and User Manual are available on: www.ridart.it/support

MAINTENANCE

- Periodically check the device is necessary to remove possible dirty.
- Always replace the product after fire, deflagration, brake or damage.
- In case of tampering warranty expires and safety protection is not guaranteed.

YOU MAY ALSO BE INTERESTED IN:

| CODE | DESCRIPTION | |
|---------------------|--|--|
| 1524-01 EN P | Vapor Recovery Adaptor with deflagration flame arrester 3"F X 4" M CAMLOCK | |
| 1534-00 EN P | Vapor Recovery Adaptor with deflagration flame arrester 3"F X 3" M CAMLOCK | |
| 1528-08 | CAP Camlock 4" black | |

RIDART s.r.l. via Adua, 17 - 21045 Gazzada Schianno (VA) ITALY P.IVA/C.F. IT 01454770122
www.ridart.it info@ridart.it +39 0332 463301

Product Certification, Declaration of Conformity, User Manual and Testing on: www.ridart.it/support
The Data and Images are not binding. We reserve the right to make changes without notice. Pressure & Flow Tolerances ±20%.